



CONTURO

Sediul Birourii, Depozit, Service Etansari: 110183 Pitesti, Str. Intrarea Abatorului, Nr. 23
Telefon/Fax: 0248 285067 ; 0248 615201 Telefon Mobil: 0722 224711 ; 0745 150704
Email : conturo@clicknet.ro, conturo.ind@clicknet.ro
www.conturo.ro www.etansari-mecanice.ro



Parametri de funcționare

- Medii de etansat: Apa, ulei, medii slab corozive
- Temperatură: -20°C ~ 200°C
- Presiune: ≤ 5 bar
- Viteză: ≤ 5 m/sec

	d	D	D1	L1	L2
216-20	20	42.5	55.5	11	25.7
216-22	22	47	45.5	9	23.8
216-25	25	54	50.5	10	28.8
216-28	28	54	50.5	10	28.8
216-30	30	54	50.5	10	28.8
216-35	35	62	60.5	11	29

Etanșare Mecanică tip 216



Materiale Componente Etanșări

• Inel Staționar

- Carbură de Siliciu (SiC)
- Carbură de Tungsten (TC)

• Inel Rotativ

- Carbură de Siliciu (SiC)
- Carbură de Tungsten (TC)

• Etanșare Secundară

- cauciuc Nitrilic (NBR)
- cauciuc EPDM
- cauciuc Fluoroelastomeric (VITON@)

• Arcuri (Arc) și alte componente metalice

- Arc și carcasa etanșare (oțel + plastic sau aliaje aluminiu)